the throng the entire that the entire become

1. Name of Procuring Agency:

University of Health Sciences Lahore

2. Method of Procurement:

Single Stage two Envelopes

3. Title of Procurement:

Procurement of Laboratory Equipment for immunology Department, University of Health Sciences, Lahore

4. Tender Inquiry No:

UHS/PUR/1405/21

5. Date & Time of Bid Closing:

22-03-2022 at 11:00 AM

6. Date & Time of Bid Opening:

22-03-2022 at 11:30 AM

7. No. of bids received:

<u>10</u>

| | Specifications | Weklin Hitech | Muslim Medical Services | Sure Bio Diagnostic & Pharmacy | Nadeem Traders | The Worldwide Scientific | Sind Medical Stores | New Chemical Center | H.A. Shah & Sons | Pakistan Scientific Traders | Pak Glorious Enterprises |
|---------------|---|--|-------------------------------|---|--|---|--|---|---------------------|--|--|
| Freezer (-80) | Vertical Type Origin: USA, EU equivalent Capacity: 570 Liters No of compressors: 2 No of internal doors: 5 Temperature range: upto -50 to -86 C or better Non-Corrosive, Non-Flammable, Non- Explosive Noise Level < 57.7 Db(A) or less Safety Features: Automatic vent port Commercial availability of gas in Pakistan Market:Yes Cooling Liquid: Green cooling liquid Pull down to -80 C: <4 Hour & 10 min or better Freezer must have Special low-temperature outer door seals allow gaskets to remain flexible at -86 °C and prevents ice buildup Compressor: Dual compressor with preventive Oil logging Voltage Compensation: Buck/Boost - voltage stabilizer option CE and UL certified & REACH + RoHS compliant along with ENERGY STAR partner Certificates of Foreign Trained Engineers Accessories: 5 KVA Voltage Stabilizer | Not Qualified Required Capacity is less than 570L, Compressors are 1 instead of 2, Internal door is 1 instead of 5 | Qualified | Not Quoted | Not Qualified Internal Doors are 2 instead of 5, Automatic vent port not mentioned | Not Qualified Internal doors are 2 instead of 5 Automatic vent port, Pull dowm Temperature is not mentioned | Not Qualified, Compressors are 1 instead of 2, | Not Qualified, Internal doors are 2 instead of 5. Pull dowm Temperature, is not mentioned. | Qualified | Not Qualified, Stabilizer is not quoted safety vent, Pull dowm Temperature, are not mentioned | Not Qualified, AJKL;' Stabilizer is not quoted safety vent, Pull dowm Temperature, are not mentioned. |
| Mini Spin | 8 place 1.51 - 2.0 m1 microtube rotor and PCR rotor Compact design Whisper quiet operation Should have quick spin downs of microtubes and PCR tubes Simply close the lid for acceleration and open the lid for deceleration, or use the on/off switch Max. Speed [rpm]: 7000 Max. RCF[xg]: 2680xg Rotor Capacity: 0.2/0.5/1.5/2.0mlx8; 0.2mLx16 PCR | Qualified | Not Quoted | Not Qualified speed is less then quoted | Qualified | Qualified | Not Quoted | Qualified | Not Quoted | Not Quoted | Qualified e 1 2 |

| | Power: 240V Noise level(dB): <45 | | | | | | | | | | |
|---|--|---------------|-------------------------------|--------------------------------------|----------------|--|------------------------|--|---------------------|-----------------------------------|-----------------------------|
| Item | Specifications | Weklin Hitech | Muslim Medical Services | Sure Bio Diagnostic & Pharmacy | Nadeem Traders | The Worldwide Scientific | Sind Medical Stores | New Chemical Center | H.A. Shah & Sons | Pakistan Scientific Traders | Pak Glorious Enterprises |
| Liquid Nitrogen Container (Portable) | Capacity (4-6L) ,Container with Canisters, High strength, light weight and small size aluminum structure; Equipped with belt; Ultra low evaporation loss; Number coding for canister place, Lockable lid | Qualified | Not Quoted | Not Quoted | Qualified | Not Qualified Capacity is larger than required, difficult to carry | Not Quoted | Not Qualified Capacity is larger than required, difficult to carry | Not Quoted | Not Quoted | Not Quoted |
| Homogenizer | Capacity 0.25 to 50 ml Speed Range5,000 to 35,000 rpm Accessories Battery, Charger, Probes, Stand and Tool Kit Display Digital / Scale Power 110 / 220 Volts CE Certified | Qualified | Not Quoted | Not Quoted | Qualified | Qualified | Not Quoted | Qualified | Not Quoted | Not Quoted | Qualified |
| Set of Micropipettes 0-2.5ul, 0.5-10ul, 10-100ul, 100- 1000ul, Multichannel (50- 450ul) | Fully autoclavable (121"Cfor 20 minutes) Enhanced UV resistance Hyper blower system, Reference grade The pipette must have calibration/adjustment window along with volume window. The Pipette should have 4 digit displays. The pipette should have spring loaded tip cone. The material of the piston should be Fortron/PEI Fortron Calibration key along with the pipette. | Qualified | Not Quoted | Qualified | Qualified | Not Qualified Multichannel is not Quoted | Not Quoted | Qualified | Qualified | Not Quoted | Qualified |

All technical bid was evaluated by EndUsers against the laid specifications and comparative statement (summary/detail) is being submitted to Technical committee for further necessary action.

Dr. Shah Jahan Head, Department of Immunology

No Complaint Shall be entertained after 07 days of display of Technical Evaluation report.

Dr. Uruj ZehraConvener

Lt.Col. (R). Dr. Khalid Rahim

Member

Dr. Allah Rakha Member